
目录

前言	1.1
可执行文件格式概览	1.2
通用内容	1.3
常见格式	1.4
COFF	1.4.1
PE	1.4.2
ELF	1.4.3
Mach-O	1.4.4
相关工具	1.5
file	1.5.1
LIEF	1.5.2
LIEF用法举例	1.5.2.1
Mach-O	1.5.2.1.1
Android	1.5.2.1.2
OAT	1.5.2.1.2.1
ELF	1.5.2.1.3
libtacker.so	1.5.2.1.3.1
子教程	1.6
附录	1.7
参考资料	1.7.1

可执行文件格式

- 最新版本: v0.8.3
- 更新时间: 20231007

简介

介绍常用的可执行文件格式，先是概览；然后是通用内容；接着介绍常见格式，包括早期通用的COFF、Windows的PE、Linux/Android的ELF、macOS/iOS的Mach-O，以及相关的工具，比如查看格式的file，和解析格式的LIEF，且给出具体用法实例，包括解析Mach-O、解析Android的OAT、解析ELF；以及相关子教程。

源码+浏览+下载

本书的各种源码、在线浏览地址、多种格式文件下载如下：

HonKit源码

- [crifan/executable_file_format](#): 可执行文件格式

如何使用此HonKit源码去生成发布为电子书

详见：[crifan/honkit_template: demo how to use crifan honkit template and demo](#)

在线浏览

- 可执行文件格式 [book.crifan.org](#)
- 可执行文件格式 [crifan.github.io](#)

离线下载阅读

- 可执行文件格式 PDF
- 可执行文件格式 ePub
- 可执行文件格式 Mobi

版权和用途说明

此电子书教程的全部内容，如无特别说明，均为本人原创。其中部分内容参考自网络，均已备注了出处。如发现有侵权，请通过邮箱联系我 [admin](#) 艾特 [crifan.com](#)，我会尽快删除。谢谢合作。

各种技术类教程，仅作为学习和研究使用。请勿用于任何非法用途。如有非法用途，均与本人无关。

鸣谢

感谢我的老婆陈雪的包容理解和悉心照料，才使得我 crifan 有更多精力去专注技术专研和整理归纳出这些电子书和技术教程，特此鸣谢。

其他

作者的其他电子书

本人 crifan 还写了其他 150+ 本电子书教程，感兴趣可移步至：

[crifan/crifan_ebook_readme: Crifan的电子书的使用说明](#)

关于作者

关于作者更多介绍，详见：

[关于CrifanLi李茂 – 在路上](#)

crifan.org，使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新：
2023-10-07 23:42:14

可执行文件格式概览

可执行文件格式，常见的有很多种。

此处只至少其中相对常见的：


背景知识

文件后缀和格式

- 文件后缀和格式
 - 库文件
 - 动态库文件
 - Win: `.dll`
 - Linux/Android: `.so`
 - 相关：目标文件: `.o`
 - Mac: `.dylib`
 - 静态库文件
 - Win: `.lib`
 - Linux: `.a`
 - Mac: `.a`
 - 可执行文件
 - Win: `.exe`
 - Linux/Android: 无后缀
 - Mac: `.app` 或 无后缀

可执行文件格式和文件后缀

- 可执行文件格式和文件后缀
 - 可执行文件格式发展历史关系图
 - 离线查看



- 在线浏览

- [可执行文件格式发展历史关系图](#) | [ProcessOn免费在线作图](#)

○ 概述

- 早期的: `a.out`、通用的 `COFF`
- 目前主流的:
 - Win : `PE`
 - 相关文件: `.exe` 可执行文件、`.dll` 动态库
 - Linux 和 Android : `ELF`
 - 相关文件: 无后缀 可执行文件、`.so` 动态库、`.o` 目标文件
 - macOS / iOS : `Mach-0`
 - 相关文件: 无后缀 可执行文件、`.dylib` 动态库、`.o` 目标文件

○ 详解

- 早期的
 - Microsoft
 - `MZ` : DOS 中的 `.exe`
 - `MZ` = Mark Zbikowski : MS-DOS主要开发者之一
 - UNIX系统
 - 最早的
 - `a.out`
 - = assembler output
 - 后来通用的
 - `COFF`
- 目前主流的
 - Microsoft系的: `PE`
 - 常见系统: Windows
 - 常见后缀: `.exe`
 - 相关的: 动态链接库的 `.dll`
 - Linux系的: `ELF`
 - 常见系统: Linux 各个发行版 (`Ubuntu`、`CentOS` 等)、(基于Linux改造的) `Android`
 - 常见后缀: 无
 - 相关的: 动态链接库的 `.so`、目标文件的 `.o`
 - Apple系的: `Mach-0`
 - 常见系统: `macOS` / `iOS` / `watchOS` / `tvOS`
 - 常见后缀: 无
 - 相关的: 动态链接库的 `.dylib`

crifan.org, 使用[署名4.0国际\(CC BY 4.0\)协议](#)发布 all right reserved, powered by Gitbook最后更新:
2023-09-19 22:55:59

通用内容

核心点和通用点

不同可执行文件格式的内部，最核心的是：

- 编译和链接的过程
 - 涉及到编译器和链接器
 - 如何生成代码？
 - 把生成的代码和数据，放到什么地方？
 - 运行时如何加载这些代码和数据？
 - 才能确保程序能正常执行

不用文件格式的通用内容

- 各种的
 - Segment段
 - 代码段
 - `.text`
 - 数据段
 - `.data`
 - 等等
 - section区
 - `.bss`
 - `.data`
 - `.rodata`
 - 等等

函数调用逻辑

When a program wants to call a function, it actually does following flow:

- 1.It made a jump to relevant entry in PLT (Procedure Linkage Table)
- 2.In PLT, there is another jump to an address mentioned in related entry in GOT (Global Offset Table)
- 3.If this is the first the function is called, follow step #4. If this isn't, follow step #5.
- 4.The related GOT entry contains an address that points back to next instruction in PLT. Program will jump to this address and then calls the dynamic linker to resolve the function's address. If the function is found, its address is put in related GOT entry and then the function itself is executed.
 - So, another time the function is called, GOT already holds its address and PLT can jump directly to the address. This procedure is called lazy binding; all external symbols are not resolved until the time it is really needed (in this case, when a function is called). Jump to step #6
- 5.Jump to the address mentioned in GOT. It is the address of the function thus PLT is no longer used
- 6.Execution of the function is finished. Jump back to the next instruction in the main program.

->

- 1.跳转到PLT=Procedure Linkage Table中的对应入口
- 2.PLT中还有另外一个跳转，跳转到GOT=Global Offset Table中相关的入口
- 3.如果函数找到了被调用了，则继续步骤4，否则继续步骤5
- 1. GOT入口中包括了一个地址，指向了PLT中的下一个指令
 2. 程序会调到转该指令，谈话调用动态链接器去继续函数地址。
 - 如果函数找到了，则该函数地址被放到GOT入口中，然后函数自己被执行
 3. 如果下一次函数被执行时，GOT中已有其地址，所以PLT可以直接跳转到对应地址
 - 此过程叫做懒绑定lazy binding
 - 所有外部符号都不会去解析，直到去真正要执行之前，需要解析，才去解析
- 5.跳转到GOT中提到的函数的地址。所以就不用PLT了。
- 执行函数，直到结束。跳转会主程序中的下一个指令。

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-10-02 17:23:02

常见格式

此处介绍常见的可执行文件格式：

- 早期通用的： `COFF`
- 目前主流的：
 - Win 的： `PE`
 - Linux / Android 的： `ELF`
 - macOS / iOS 的： `Mach-O`

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-09-19 21:57:52

COFF

- COFF = Common Object File Format = 通用对象文件格式

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-09-19 21:58:21

PE

- PE = Portable Executable


crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-09-19 22:54:27

ELF


- ELF = Executable and Linking Format = 可执行和链接格式
 - 按类型分
 - Relocatable File = 可重定位文件
 - A relocatable file holds code and data suitable for linking with other object files to create an executable or a shared object file.
 - Executable File = 可执行文件
 - An executable file holds a program suitable for execution
 - Shared Object File = 共享对象文件
 - A shared object file holds code and data suitable for linking in two contexts. First, the link editor may process it with other relocatable and shared object files to create another object file.
 - Second, the dynamic linker combines it with an executable file and other shared objects to create a process image
 - ELF格式概览
 - 图

Object File Format

Linking View



Execution View



- 详见子教程
 - [可执行文件格式: ELF](#)

Mach-O

- Mach-O = Mach Object
 - Mach-O 是 Mac 和 iOS 等Apple平台中的[可执行文件格式](#)
 - 详见子教程
 - [可执行文件格式: Mach-O](#)

crifan.org, 使用[署名4.0国际\(CC BY 4.0\)协议](#)发布 all right reserved, powered by Gitbook最后更新:
2023-10-07 23:41:47

相关工具

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-09-19 22:00:06

file

- `file`
 - 是个命令行工具，可以在 Linux / Android 和 macOS / iOS 中查看文件的格式

举例

Mac

- rsync

```
→ bin pwd
/usr/local/Cellar/rsync/3.2.7_1/bin

→ bin file rsync
rsync: Mach-O 64-bit executable x86_64
```

- readelf

```
→ ~ file /opt/homebrew/opt/binutils/bin/readelf
/opt/homebrew/opt/binutils/bin/readelf: Mach-O 64-bit executable arm64
```

- python64.dylib

```
→ plugins pwd
/Applications/IDA Pro 7.0/ida.app/Contents/MacOS/plugins
→ plugins ll
total 33776
...
-rw-r--r--@ 1 crifan admin 113K  9 14 2017 python.dylib
-rw-r--r--@ 1 crifan admin 113K  9 14 2017 python64.dylib
...

→ plugins file python64.dylib
python64.dylib: Mach-O 64-bit dynamically linked shared library x86_64
```

FAT格式

- FAT格式的rsync

```
→ ~ which rsync
/usr/bin/rsync
→ ~ file /usr/bin/rsync
/usr/bin/rsync: Mach-O universal binary with 2 architectures: [x86_64:Mach-O 64-bit executable x86_64] [arm64e:Mach-O 64-bit executable arm64e]
/usr/bin/rsync (for architecture x86_64): Mach-O 64-bit executable x86_64
/usr/bin/rsync (for architecture arm64e): Mach-O 64-bit executable arm64e
```

更多例子详见：

FAT举例 · 可执行文件格式: Mach-O (crifan.org)

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-10-07 23:40:46

LIEF

- LIEF
 - 介绍：用于查看和解析（ELF / MachO / PE / Android 等）各种通用的可执行文件格式的库
 - 一句话描述：Library to Instrument Executable Formats
 - 支持格式
 - ELF
 - PE
 - MachO
 - Android
 - DEX
 - OAT
 - ART
 - VDEX
 - 主页
 - [LIEF](#)
 - [图](#)

LIEF

Home Blog Download Documentation About Sponsor

LIEF : Library to Instrument Executable Formats

This project aims at providing a cross platform library to parse, modify and abstract ELF, PE and MachO formats.

DOWNLOAD DOCUMENTATION

LATEST VERSION: 0.13.2 (4 MONTHS AGO)

- 文档
 - [Welcome to LIEF's documentation! — LIEF Documentation](#)
- 下载
 - [LIEF](#)

安装

- Mac

```
pip install lief
```

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-10-04 15:25:15

LIEF用法举例

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-10-04 15:39:24

LIEF解析Mach-O

从 Mach-O 中解析 `__text`、`__data` 等section的内容：

```
import lief

# --- Extract __text and __data section content from the binary ---
binary = lief.parse("uncrackable.arm64")
text_section = binary.get_section("__text")
text_content = text_section.content

data_section = binary.get_section("__data")
data_content = data_section.content
```

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-10-04 16:56:15

Android

此处举例说明，如何用LIEF去解析Android的相关格式。

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-10-04 16:58:38

LIEF解析Android的OAT

此处用例子说明，如何用LIEF解析Android的OAT格式文件：

代码：

```
import lief

oat = lief.parse("SomeOAT")
for s in oat.dynamic_symbols:
    print(s)
```

输出：

oatdata	OBJECT	GLOBAL	1000	1262000
oatexec	OBJECT	GLOBAL	1263000	10d4060
oatlastword	OBJECT	GLOBAL	233705c	4
oatbss	OBJECT	GLOBAL	2338000	f5050
oatbsslastword	OBJECT	GLOBAL	242d04c	4

crifan.org，使用署名4.0国际(CC BY 4.0)协议发布 all right reserved，powered by Gitbook最后更新：
2023-10-04 16:59:20

LIEF解析ELF

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-10-04 16:59:42

LIEF修改ELF的libtacker.so

此处举例说明LIEF的用法：

- 用LIEF解析修改ELF格式的so库文件：`libtacker.so`

基本用法：打印解析后对象的信息

代码：

```
import lief

libtackerObj = lief.parse('modifyElf/input/libtacker_arm64_v8a.so')
print("libtackerObj=", libtackerObj)
```

输出：

```
→ libtacker_so python modifyElf/modifyLibtackerSo.py
inputElfFile= modifyElf/input/libtacker_armeabi_v7a.so
inputFileName= libtacker_armeabi_v7a.so
pureFileName %s, fileExt %s ('libtacker_armeabi_v7a', '.so')
Loaded file: modifyElf/input/libtacker_armeabi_v7a.so
libtackerElf= Header
=====
Magic:                7f 45 4c 46
Class:                CLASS32
Endianness:          LSB
Version:              CURRENT
OS/ABI:               SYSTEMV
ABI Version:          0
Machine type:         ARM
File type:             DYNAMIC
Object file version:  CURRENT
Entry Point:          0xb9c8
Program header offset: 0x34
Section header offset: 815008
Processor Flag:       83886592 SOFT_FLOAT EABI_VER5
Header size:          52
Size of program header: 32
Number of program header: 9
Size of section header: 40
Number of section headers: 27
Section Name Table idx: 26

Sections
=====
          NULL          0          0          0          0
.note.android.ident NOTE    154         98         154         1.09412  ALLOC
          LOAD NOTE
.note.gnu.build-id  NOTE     1ec          24          1ec         4.13606  ALLOC
          LOAD NOTE
```

.dynsym	DYNSYM	210	6d0	210	3.54702	ALLOC
	LOAD					
.gnu.version	HIOS	8e0	da	8e0	1.48975	ALLOC
	LOAD					
.gnu.version_r	GNU_VERNEED	9bc	40	9bc	2.16157	ALLOC
	LOAD					
.gnu.hash	GNU_HASH	9fc	1ec	9fc	6.3602	ALLOC
	LOAD					
.hash	HASH	be8	370	be8	1.38896	ALLOC
	LOAD					
.dynstr	STRTAB	f58	b8f	f58	4.66594	ALLOC
	LOAD					
.rel.dyn	REL	1ae8	2dd0	1ae8	3.36673	ALLOC
	LOAD					
.ARM.exidx	ARM_EXIDX	48b8	1ad8	48b8	5.18866	ALLOC LINK_O
RDER	LOAD ARM_UNWIND					
.rel.plt	REL	6390	120	6390	3.54485	ALLOC INFO_L
INK	LOAD					
.ARM.extab	PROGBITS	64b0	334c	64b0	4.80098	ALLOC
	LOAD					
.rodata	PROGBITS	97fc	21c7	97fc	5.26982	ALLOC MERGE
STRINGS	LOAD					
.text	PROGBITS	b9c8	b72c4	b9c8	6.55022	ALLOC EXECIN
STR	LOAD					
.plt	PROGBITS	c2c90	260	c2c90	3.78829	ALLOC EXECIN
STR	LOAD					
.data.rel.ro	PROGBITS	c3ef0	1790	c2ef0	4.42226	WRITE ALLOC
	LOAD GNU_RELRO					
.fini_array	FINI_ARRAY	c5680	8	c4680	1.75	WRITE ALLOC
	LOAD GNU_RELRO					
.init_array	INIT_ARRAY	c5688	114	c4688	-0	WRITE ALLOC
	LOAD GNU_RELRO					
.dynamic	DYNAMIC	c579c	e8	c479c	3.17459	WRITE ALLOC
	LOAD DYNAMIC GNU_RELRO					
.got	PROGBITS	c5884	70	c4884	3.63662	WRITE ALLOC
	LOAD GNU_RELRO					
.got.plt	PROGBITS	c58f4	9c	c48f4	1.98777	WRITE ALLOC
	LOAD GNU_RELRO					
.data	PROGBITS	c6990	2410	c4990	7.22773	WRITE ALLOC
	LOAD					
.bss	NOBITS	c8da0	22d	c6da0	5.11609	WRITE ALLOC
	LOAD					
.comment	PROGBITS	0	c6	c6da0	5.05236	MERGE STRING
S						
.ARM.attributes	ARM_ATTRIBUTES	0	3c	c6e66	4.587	
.shstrtab	STRTAB	0	fe	c6ea2	4.2632	
Segments						
=====						
PHDR	r--	34	34	34	120	120 4
LOAD	r-x	0	0	0	c2ef0	c2ef0 1000
Sections in this segment ↓						
						.note.android.ident
						.note.gnu.build-id
						.dynsym

```

.gnu.version
.gnu.version_r
.gnu.hash
.hash
.dynstr
.rel.dyn
.ARM.exidx
.rel.plt
.ARM.extab
.rodata
.text
.plt

LOAD                rw-          c2ef0      c3ef0      c3ef0      1aa0      1aa0      1000
Sections in this segment ↓
.data.rel.ro
.fini_array
.init_array
.dynamic
.got
.got.plt

LOAD                rw-          c4990      c6990      c6990      2410      263d      1000
Sections in this segment ↓
.data
.bss

DYNAMIC             rw-          c479c      c579c      c579c      e8         e8         4
Sections in this segment ↓
.dynamic

GNU_RELRO           r--          c2ef0      c3ef0      c3ef0      1aa0      2110      1
Sections in this segment ↓
.data.rel.ro
.fini_array
.init_array
.dynamic
.got
.got.plt

GNU_STACK           rw-          0           0           0           0           0           0

NOTE                r--          154        154        154         bc         bc         4
Sections in this segment ↓
.note.android.ident
.note.gnu.build-id

ARM_UNWIND          r--          48b8      48b8      48b8      1ad8      1ad8      4
Sections in this segment ↓
.ARM.exidx

Dynamic entries
=====
NEEDED              b71         liblog.so
NEEDED              b7b         libm.so

```



```

memchr          FUNC      GLOBAL      0          0          LIBC      (2)
__vsprintf_chk  FUNC      GLOBAL      0          0          LIBC      (2)
pthread_mutex_lock  FUNC      GLOBAL      0          0          LIBC      (2)
calloc          FUNC      GLOBAL      0          0          LIBC      (2)
pthread_mutex_unlock  FUNC      GLOBAL      0          0          LIBC      (2)
strcmp         FUNC      GLOBAL      0          0          LIBC      (2)
pthread_getspecific  FUNC      GLOBAL      0          0          LIBC      (2)
memset         FUNC      GLOBAL      0          0          LIBC      (2)
pthread_once   FUNC      GLOBAL      0          0          LIBC      (2)
pthread_setspecific  FUNC      GLOBAL      0          0          LIBC      (2)
memcpy        FUNC      GLOBAL      0          0          LIBC      (2)
pthread_key_delete  FUNC      GLOBAL      0          0          LIBC      (2)
pthread_key_create  FUNC      GLOBAL      0          0          LIBC      (2)
memmove       FUNC      GLOBAL      0          0          LIBC      (2)
fprintf       FUNC      GLOBAL      0          0          LIBC      (2)
fflush       FUNC      GLOBAL      0          0          LIBC      (2)
dl_unwind_find_exidx  FUNC      GLOBAL      0          0          LIBC      (3)
.datadiv_decode8345671930506918460FUNC      GLOBAL      28ec9      2384      * Global *
.datadiv_decode17898716361002246085FUNC      GLOBAL      69a59      eee      * Global *
...
.datadiv_decode18430821605022316503FUNC      GLOBAL      9c47d      1044      * Global *
JNI_OnLoad     FUNC      GLOBAL      b2bcd      48c      * Global *
.datadiv_decode9810505568447265400FUNC      GLOBAL      18c81      33e8      * Global *
...
.datadiv_decode3623259086264565478FUNC      GLOBAL      89201      8e6      * Global *

Static symbols
=====

Symbol versions
=====
* Local *
LIBC(2)
LIBC(2)
* Global *
LIBC(2)
LIBC(2)
...
LIBC(2)
LIBC(3)
* Global *
...
* Global *

Symbol versions definition
=====

Symbol version requirement
=====
1 libdl.so
1 libc.so

Dynamic relocations
=====
c3ef0    RELATIVE  32  0          0          DYNAMIC
c3ef4    RELATIVE  32  0          0          DYNAMIC

```

```

c3ef8    RELATIVE 32 0    0    DYNAMIC
...
c8d9c    RELATIVE 32 0    0    DYNAMIC
c5884    GLOB_DAT 32 0    5    DYNAMIC  __stack_chk_guard
c58a8    GLOB_DAT 32 0   12    DYNAMIC  __sF
c56ac    ABS32   32 0   27    DYNAMIC  .datadiv_decode834567193050691846
0
c56fc    ABS32   32 0   28    DYNAMIC  .datadiv_decode178987163610022460
85
c573c    ABS32   32 0   29    DYNAMIC  .datadiv_decode185723924818675064
6
...
c5738    ABS32   32 0   6c    DYNAMIC  .datadiv_decode362325908626456547
8

```

.plt.got relocations

```

=====
c5900    JUMP_SLOT 32 0    1    PLTGOT  __cxa_finalize
c5904    JUMP_SLOT 32 0    2    PLTGOT  __cxa_atexit
c5908    JUMP_SLOT 32 0    3    PLTGOT  __android_log_print
c590c    JUMP_SLOT 32 0    4    PLTGOT  __stack_chk_fail
c5910    JUMP_SLOT 32 0    6    PLTGOT  __strncpy_chk2
c5914    JUMP_SLOT 32 0    7    PLTGOT  strncpy
c5918    JUMP_SLOT 32 0    8    PLTGOT  strncat
c591c    JUMP_SLOT 32 0    9    PLTGOT  pthread_self
c5920    JUMP_SLOT 32 0    a    PLTGOT  malloc
c5924    JUMP_SLOT 32 0    b    PLTGOT  free
c5928    JUMP_SLOT 32 0    c    PLTGOT  posix_memalign
c592c    JUMP_SLOT 32 0    d    PLTGOT  abort
c5930    JUMP_SLOT 32 0    e    PLTGOT  vfprintf
c5934    JUMP_SLOT 32 0    f    PLTGOT  fputc
c5938    JUMP_SLOT 32 0   10    PLTGOT  vasprintf
c593c    JUMP_SLOT 32 0   11    PLTGOT  __assert2
c5940    JUMP_SLOT 32 0   13    PLTGOT  strlen
c5944    JUMP_SLOT 32 0   14    PLTGOT  realloc
c5948    JUMP_SLOT 32 0   15    PLTGOT  __strlen_chk
c594c    JUMP_SLOT 32 0   16    PLTGOT  memchr
c5950    JUMP_SLOT 32 0   17    PLTGOT  __vsnprintf_chk
c5954    JUMP_SLOT 32 0   18    PLTGOT  pthread_mutex_lock
c5958    JUMP_SLOT 32 0   19    PLTGOT  calloc
c595c    JUMP_SLOT 32 0  1a    PLTGOT  pthread_mutex_unlock
c5960    JUMP_SLOT 32 0  1b    PLTGOT  strcmp
c5964    JUMP_SLOT 32 0  1c    PLTGOT  pthread_getspecific
c5968    JUMP_SLOT 32 0  1d    PLTGOT  memset
c596c    JUMP_SLOT 32 0  1e    PLTGOT  pthread_once
c5970    JUMP_SLOT 32 0  1f    PLTGOT  pthread_setspecific
c5974    JUMP_SLOT 32 0  20    PLTGOT  memcpy
c5978    JUMP_SLOT 32 0  21    PLTGOT  pthread_key_delete
c597c    JUMP_SLOT 32 0  22    PLTGOT  pthread_key_create
c5980    JUMP_SLOT 32 0  23    PLTGOT  memmove
c5984    JUMP_SLOT 32 0  24    PLTGOT  fprintf
c5988    JUMP_SLOT 32 0  25    PLTGOT  fflush
c598c    JUMP_SLOT 32 0  26    PLTGOT  dl_unwind_find_exidx

```

Notes

=====


```

Note #0
-----
Name:           Android
Type:           ABI_TAG
Description:    [15 00 00 00 72 32 34 00 00 00 00 00 00 00 00 ...]

Note #1
-----
Name:           GNU
Type:           BUILD_ID
Description:    [fa 8a 30 55 6b db 44 9a 4a 2f 1f 83 46 6d 93 44 ...]
ID Hash:       fa8a30556bdb449a4a2f1f83466d9344fdef3fb5

GNU Hash Table
=====
0x6000022d2e80

SYSV Hash Table
=====
0x600001381b40

```

复杂用法：修改 `.comment` 内容为随机乱码

代码：

- `modifyElf/modifyLibtackerSo.py`

```

# Function: mofidy libtacker so (arm64_v8a, armeabi_v7a) comments section content the o
utput to new one
# Author: Crifan Li
# Update: 20230912

import os
import random
import string
import lief

#####
# input & config
#####

# intputElfFile = "modifyElf/input/libtacker_arm64_v8a.so"
inputElfFile = "modifyElf/input/libtacker_armeabi_v7a.so"
print("intputElfFile=", inputElfFile)

outputFoler = "modifyElf/output"

TotalRandomTime = 40
OutputSuffixStartNum = 20

#####
# generate output file name

```

```

#####

inputFileName = os.path.basename(inputElfFile)
print("inputFileName=", inputFileName)
pureFileName, fileExt = os.path.splitext(inputFileName)
print("pureFileName=%s, fileExt=%s", (pureFileName, fileExt)) # pureFileName=%s, fileExt=%s ('libtacker_arm64_v8a', '.so')

#####
# Main
#####

libtackerElf = lief.parse(inputElfFile)
print("Loaded file: ", inputElfFile)
# print("libtackerElf=", libtackerElf)
print("header=", libtackerElf.header)
print("imported_functions=", libtackerElf.imported_functions)
print("exported_functions=", libtackerElf.exported_functions)

for section in libtackerElf.sections:
    print("-" * 20) # section's name
    print("name=", section.name) # section's name
    print("size=", section.size) # section's size
    contentLen = len(section.content)
    print("contentLen=", contentLen) # Should match the previous print

commentSection = libtackerElf.get_section(".comment")

print("\n\n")

print("+++ Start total %d round overwrite .comment section content with random char" %
TotalRandomTime)

ContentCharNum = commentSection.size
print("ContentCharNum=", ContentCharNum)

RamdonCharRange = string.ascii_letters + string.digits
print("RamdonCharRange=", RamdonCharRange)

for curRandomTimeIdx in range(TotalRandomTime):
    curRandomTime = curRandomTimeIdx + 1
    print("%s Random Time [%d] %s" % ("-" * 30, curRandomTime, "-" * 30))

    # randomCharList = random.sample(RamdonCharRange, 198)

    randomCharList = []
    for randomCharIdx in range(ContentCharNum):
        curRandomChar = random.choice(RamdonCharRange)
        randomCharList.append(curRandomChar)
    print("randomCharList=", randomCharList)

    # randomCharBytes = bytes(randomCharList)
    randomStr = "".join(randomCharList)
    print("randomStr=", randomStr)
    randomCharBytes = bytes(randomStr, "utf-8")

```

```

print("randomCharBytes=", randomCharBytes)
newContentBytes = randomCharBytes

print("before: commentSection.content=", commentSection.content)

# num0 = 0x30
# print("commentSection.contentType=", type(commentSection.content))
# newContentBytes = bytes([num0] * commentSection.size)

newContentMemoryView = memoryview(newContentBytes)
# print("newContentMemoryView type=", type(newContentMemoryView))
commentSection.content = newContentMemoryView
print("after: commentSection.content=", commentSection.content)

# outputElfFile = "modifyElf/output/libtacker_arm64_v8a_changedComment.so"
# outputElfFile = "modifyElf/output/libtacker_arm64_v8a_changedComment_%d.so" % curRandomTime
suffixNum = OutputSuffixStartNum + curRandomTime
outputFileName = "%s_changedComment_%d%s" % (pureFileName, suffixNum, fileExt)
outputElfFile = os.path.join(outputFolder, outputFileName)

libtackerElf.write(outputElfFile)
print("Saved to", outputElfFile)

```

- 输出log日志

```

Loaded file: modifyElf/input/libtacker_arm64_v8a.so
header= Magic:          7f 45 4c 46
Class:                 CLASS64
Endianness:            LSB
Version:               CURRENT
OS/ABI:                SYSTEMV
ABI Version:           0
Machine type:          AARCH64
File type:              DYNAMIC
Object file version:   CURRENT
Entry Point:           0x1a5c0
Program header offset: 0x40
Section header offset: 848344
Processor Flag:        0
Header size:           64
Size of program header: 56
Number of program header: 9
Size of section header: 64
Number of section headers: 27
Section Name Table idx: 26

imported_functions= [<lief._lief.Function object at 0x104876f0>, <lief._lief.Function
object at 0x104877230>, <lief._lief.Function object at 0x104877370>, <lief._lief.Functi
on object at 0x1048772f0>, <lief._lief.Function object at 0x1048a99b0>, <lief._lief.Functi
on object at 0x104967230>, <lief._lief.Function object at 0x1049668f0>, <lief._lief.
Function object at 0x10487cc30>, <lief._lief.Function object at 0x10487cbb0>, lief._li
ef.Function object at 0x10487cc70>, <lief._lief.Function object at 0x10487ccf0>, <lief.
_lief.Function object at 0x10487ccb0>, <lief._lief.Function object at 0x10497a7f0>, <li

```

```


ef._lief.Function object at 0x104a45bf0 , lief._lief.Function object at 0x104a47c30 ,
lief._lief.Function object at 0x104a474b0 , lief._lief.Function object at 0x104a44470
, lief._lief.Function object at 0x1049fd8b0 , lief._lief.Function object at 0x1049fcab
0 , lief._lief.Function object at 0x104a7d6f0 , lief._lief.Function object at 0x104a7
ffb0 , lief._lief.Function object at 0x104a7fbf0 , lief._lief.Function object at 0x10
4a7fb70 , lief._lief.Function object at 0x104a7ebb0 , lief._lief.Function object at 0
x104a7f5b0 , lief._lief.Function object at 0x104a7efb0 , lief._lief.Function object a
t 0x104a7c7f0 , lief._lief.Function object at 0x1048e16b0 , lief._lief.Function objec
t at 0x1048e21f0 , lief._lief.Function object at 0x10492bd70 , lief._lief.Function ob
ject at 0x104929cf0 , lief._lief.Function object at 0x104a14430 , lief._lief.Function
object at 0x104a166f0 , lief._lief.Function object at 0x1049d86f0 , lief._lief.Functi
on object at 0x1049db6f0 , lief._lief.Function object at 0x10495c6f0 , lief._lief.Fu
nction object at 0x10495f1f0 , lief._lief.Function object at 0x10495ebb0 , lief._lief
.Function object at 0x104a218b0 , lief._lief.Function object at 0x104a211f0 , lief._l
ief.Function object at 0x1048f98f0 , lief._lief.Function object at 0x1049c20b0 , lief
._lief.Function object at 0x1048cfef0 , lief._lief.Function object at 0x104890370 , l
ief._lief.Function object at 0x104890f70 , lief._lief.Function object at 0x104a0f030 ]
exported_functions= [ lief._lief.Function object at 0x104876f70 , lief._lief.Function
object at 0x104877230 , lief._lief.Function object at 0x104877370 , lief._lief.Functi
on object at 0x1048772f0 , lief._lief.Function object at 0x1048a99b0 , lief._lief.Fun
ction object at 0x104967230 , lief._lief.Function object at 0x1049668f0 , lief._lief.
Function object at 0x10487cc30 , lief._lief.Function object at 0x10487cbb0 , lief._li
ef.Function object at 0x10487cc70 , lief._lief.Function object at 0x10487ccf0 , lief.
_lief.Function object at 0x10487ccb0 , lief._lief.Function object at 0x10497a7f0 , li
ef._lief.Function object at 0x104a45bf0 , lief._lief.Function object at 0x104a47c30 ,
lief._lief.Function object at 0x104a474b0 , lief._lief.Function object at 0x104a44470
, lief._lief.Function object at 0x1049fd8b0 , lief._lief.Function object at 0x1049fcab
0 , lief._lief.Function object at 0x104a7d6f0 , lief._lief.Function object at 0x104a7
ffb0 , lief._lief.Function object at 0x104a7fbf0 , lief._lief.Function object at 0x10
4a7fb70 , lief._lief.Function object at 0x104a7ebb0 , lief._lief.Function object at 0
x104a7f5b0 , lief._lief.Function object at 0x104a7efb0 , lief._lief.Function object a
t 0x104a7c7f0 , lief._lief.Function object at 0x1048e16b0 , lief._lief.Function objec
t at 0x1048e21f0 , lief._lief.Function object at 0x10492bd70 , lief._lief.Function ob
ject at 0x104929cf0 , lief._lief.Function object at 0x104a14430 , lief._lief.Function
object at 0x104a166f0 , lief._lief.Function object at 0x1049d86f0 , lief._lief.Functi
on object at 0x1049db6f0 , lief._lief.Function object at 0x10495c6f0 , lief._lief.Fu
nction object at 0x10495f1f0 , lief._lief.Function object at 0x10495ebb0 , lief._lief
.Function object at 0x104a218b0 , lief._lief.Function object at 0x104a211f0 , lief._l
ief.Function object at 0x1048f98f0 , lief._lief.Function object at 0x1049c20b0 , lief
._lief.Function object at 0x1048cfef0 , lief._lief.Function object at 0x104890370 , l
ief._lief.Function object at 0x104890f70 , lief._lief.Function object at 0x104a0f030 ,
lief._lief.Function object at 0x104a0db30 , lief._lief.Function object at 0x104896770
, lief._lief.Function object at 0x1049144b0 , lief._lief.Function object at 0x1048e553
0 , lief._lief.Function object at 0x1048ac730 , lief._lief.Function object at 0x1049a
4ef0 , lief._lief.Function object at 0x1049a5670 , lief._lief.Function object at 0x10
488b1b0 , lief._lief.Function object at 0x104993570 , lief._lief.Function object at 0
x104993fb0 , lief._lief.Function object at 0x104992f30 , lief._lief.Function object a
t 0x104a900f0 , lief._lief.Function object at 0x104a90130 , lief._lief.Function objec
t at 0x104a90170 , lief._lief.Function object at 0x104a901b0 , lief._lief.Function ob
ject at 0x104a901f0 , lief._lief.Function object at 0x104a90230 , lief._lief.Function
object at 0x104a90270 , lief._lief.Function object at 0x104a902b0 , lief._lief.Functi
on object at 0x104a902f0 , lief._lief.Function object at 0x104a90330 , lief._lief.Fu
nction object at 0x104a90370 , lief._lief.Function object at 0x104a903b0 , lief._lief
.Function object at 0x104a903f0 ]
-----
name=

```


```
size= 0
contentLen= 0
-----
name= .note.android.ident
size= 152
contentLen= 152
-----
name= .note.gnu.build-id
size= 36
contentLen= 36
-----
name= .dynsym
size= 2832
contentLen= 2832
-----
name= .gnu.version
size= 236
contentLen= 236
-----
name= .gnu.version_r
size= 64
contentLen= 64
-----
name= .gnu.hash
size= 492
contentLen= 492
-----
name= .hash
size= 952
contentLen= 952
-----
name= .dynstr
size= 3097
contentLen= 3097
-----
name= .rela.dyn
size= 34896
contentLen= 34896
-----
name= .rela.plt
size= 1104
contentLen= 1104
-----
name= .gcc_except_table
size= 6496
contentLen= 6496
-----
name= .rodata
size= 13364
contentLen= 13364
-----
name= .eh_frame_hdr
size= 7612
contentLen= 7612
-----
name= .eh_frame
```

```
size= 36052
contentLen= 36052
-----
name= .text
size= 715872
contentLen= 715872
-----
name= .plt
size= 768
contentLen= 768
-----
name= .data.rel.ro
size= 11960
contentLen= 11960
-----
name= .fini_array
size= 16
contentLen= 16
-----
name= .init_array
size= 560
contentLen= 560
-----
name= .dynamic
size= 464
contentLen= 464
-----
name= .got
size= 192
contentLen= 192
-----
name= .got.plt
size= 392
contentLen= 392
-----
name= .data
size= 9688
contentLen= 9688
-----
name= .bss
size= 2768
contentLen= 0
-----
name= .comment
size= 198
contentLen= 198
-----
name= .shstrtab
size= 260
contentLen= 260
before: commentSection.content= memory at 0x1049b5480>
commentSection contentType= <class 'memoryview'>
newContentMemoryView type= <class 'memoryview'>
after: commentSection.content= memory at 0x1049b5540>
Saved to modifyElf/output/libtacker_arm64_v8a_changedComment.so
```


- 输出文件：（一次性的批量的多个）修改后的ELF文件：



修改前后的内容对比



- .comment 修改前：

```

Contents of section .comment:
0000 4c696e6b 65723a20 4c4c4420 31342e30 Linker: LLD 14.0
0010 2e310063 6c616e67 20766572 73696f6e .1.clang version
0020 2031342e 302e3000 416e6472 6f696420 14.0.0.Android
0030 28383037 35313738 2c206261 73656420 (8075178, based
0040 6f6e2072 34333731 31326229 20636c61 on r437112b) cla
0050 6e672076 65727369 6f6e2031 342e302e ng version 14.0.
0060 31202868 74747073 3a2f2f61 6e64726f 1 (https://andro
0070 69642e67 6f6f676c 65736f75 7263652e id.google.sourc
0080 636f6d2f 746f6f6c 63686169 6e2f6c6c com/toolchain/ll
0090 766d2d70 726f6a65 63742038 36373133 vm-project 86713
00a0 34386238 31623935 66633630 33353035 48b81b95fc603505
00b0 64666338 38316234 35313033 62656531 dfc881b45103bee1
00c0 37333129 0000 731)..

```

- .comment 修改后:

```

Contents of section .comment:
0000 62464a30 35487661 384a3768 42435237 bFJ05Hva8J7hBCR7
0010 76426449 59784743 524e4d54 33744c42 vBdIYxGCRNMT3tLB
0020 304d664d 36615353 39493555 7943464d 0MfM6aSS9I5UyCFM
0030 63566348 41376b76 67427050 4b4d4f35 cVcHA7kvgBpPKM05
0040 38503143 72734d73 636e476b 6f684932 8P1CrSmscnGkohI2
0050 4561616e 72376c30 6861466c 53667858 Eaanr7l0haFlSfxX
0060 6f66684b 3646594a 43656154 77656849 ofhK6FYJCeaTwehI
0070 71766167 67653570 45627946 576b4c45 qvagge5pEbyFwkLE
0080 4a747759 4c6f474a 38554d74 71717749 JtwYLoGJ8UMtqqwI
0090 37534a4b 7a526547 396d687a 3464544a 7SJKzReG9mhZ4dTJ
00a0 67787276 6843555a 59596332 50336836 gxrvhCUZYyc2P3h6
00b0 615a3362 786c4444 526e7370 66556f54 aZ3bx1DDRnspfUoT
00c0 746e4573 3152 tnEs1R

```

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-10-04 17:00:10

子教程

此处列出相关子教程：

- [可执行文件格式](#)
 - [可执行文件格式：ELF](#)
 - [可执行文件格式：Mach-O](#)

crifan.org, 使用[署名4.0国际\(CC BY 4.0\)协议](#)发布 all right reserved, powered by Gitbook最后更新:
2023-10-04 15:18:44

附录

下面列出相关参考资料。

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-09-19 21:13:04

参考资料

- **【已解决】** 给已有libtacker.so去改动信息
- **【已解决】** 用LIEF去修改ELF的so中的部分信息
- **【整理】** Mach-O格式分析工具：LIEF
- **【整理】** 安卓相关：OTA格式
- **【已解决】** 新Mac M2 Max中如何安装x86_64版本rsync
-
- [Comparison of executable file formats - Wikipedia](#)
- [DOS MZ executable - Wikipedia](#)
- [a.out - Wikipedia](#)
- [Portable Executable - Wikipedia](#)
- [COFF - Wikipedia](#)
- [Tool Interface Standard \(TIS\) Executable and Linking Format \(ELF\) Specification Version 1.2](#)
- [Creating and using static libraries in Linux ~ codingfreak](#)
- [Better understanding Linux secondary dependencies solving with examples](#)
- [动态库与静态库的区别 \(linux vs windows vs mac\) 51CTO博客](#)动态库和静态库的区别
- [C/C++ 动态库\(dll\)与静态库\(lib\)c++编译出来的lib库和c库有什么区别—叶知秋@qqy的博客-CSDN博客](#)
- [以.a\(a为后缀\)的文件类型是啥鸭? .a是什么文件子燕若水的博客-CSDN博客](#)
- [静态库的格式there is no dynamic section in this file广敏的博客-CSDN博客](#)
- [静态库的管理与文件格式分析 - 知乎](#)
- [静态库 \(.a\) 和共享库 \(.so\) 的文件格式差异?](#)
- [Welcome to LIEF's documentation! — LIEF Documentation \(lief-project.github.io\)](#)
- [Installation and Integration — LIEF Documentation \(lief-project.github.io\)](#)
- [Tutorials — LIEF Documentation \(lief-project.github.io\)](#)
- [03 - Play with ELF symbols — LIEF Documentation \(lief-project.github.io\)](#)
- [10 - Android formats — LIEF Documentation \(archive.is\)](#)
- [Hiding Behind ART - Black Hat 2015](#)
- [Dalvik and ART](#)
- [OAT internal structures](#)
-

crifan.org, 使用署名4.0国际(CC BY 4.0)协议发布 all right reserved, powered by Gitbook最后更新:
2023-10-04 16:49:55